

## Caméra IRBOX-C2S



Photo non contractuelle

Resolution	700 TVL
Day & Night	Auto, color, B/W, EXT1, EXT2
Video System	NTSC/PAL System
Sensor	1/3" Sony EW-View 960H CCD
Number of pixel	NTSC :976Hx494V PAL :976Hx582V
Sensitivity	0 Lux (48pc LED ON)
Sync.	Internal sync/ Line in Lock
Horizontal Frequency	NTSC :15.734KHz PAL :15.625KHz
Vertical Frequency	NTSC :60Hz PAL :50Hz
Scanning	2 :1 Interlace
S/NB Ratio	≥ 52dB
Electronics Shutter	NTSC : 1/60-1/100.000 PAL : 1/50-1/100.100
Lens	Aspherical VF Lens F=2.8-12mm with Auto Iris
White balance	Auto
Backlight Compensation	On/Off
Auto Gain Control	On/Off
Gamma Correction	0.45
Video Output	1V p-p, 75Ω
Waterproof	IP67
Voltage	DC 12V±10%
Power Current	350mA (MAX) LED ON
IR LEDs	48 pc IR LEDs
IR Distance	40~45M
Dimension	240(L)x90(W)x170(H)mm
Weight	1089g
Storage Temperature	-25 +70°C
Operation Temperature	-20 +50°C